

GX440I (9.5 kW)

WWW.RuMoto.Ru - Описание типов, опций, цвета для двигателей Honda iGX440 (MTOC Manual Type Option Colour)

Model	Type Option	CHARGE COIL	CHOKE TYPE	CONTROL PANEL TYPE	CUSTO MISED	DEFLECT OR KIT	ELECTRIC STARTER	ENGINE SWITCH	GOVERNOR MODE	LABELING: CARB - EPA	LABELING: EN	NOISE REDUCTION GRID	PTO KEY TYPE	SHAFT DIAMETER	SHAFT THREAD	SUB HARNESS	SUPPLIED LOOSE	MTO REMARK
GX440IU	QBA2	3 A	AUTO CHOKE	WITH ENG. SWITCH, WITH VOL. SW	NO	YES	YES	COMBINATION SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	3 TERMINAL HARNESS	DEFLECTOR	
GX440IU	QDA2	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	QHA2	3 A	AUTO CHOKE	W/O ENG. SWITCH, W/O VOL. SW	NO	YES	YES	REMOTE COUPLER	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	QLA2	20 A	AUTO CHOKE	WITH ENG. SWITCH, WITH VOL. SW	NO	YES	YES	COMBINATION SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	WITHOUT	DEFLECTOR	
GX440IU	QLC2	20 A	AUTO CHOKE	WITH ENG. SWITCH, WITH VOL. SW	YES		YES	COMBINATION SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF			Biemmedue + wiring harness switch mode/volume sw.□
GX440IU	QNA2	20 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	SWITCH MODE 1	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	3 TERMINAL HARNESS	DEFLECTOR	
GX440IU	QPA2	20 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	YES	YES	YES	COMBINATION SWITCH	SWITCH MODE 3	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	Hinowa Switch mode 3: 2200, 1500, 3600
GX440IU	QQA2	20 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	QTA2	20 A	AUTO CHOKE	W/O ENG. SWITCH, W/O VOL. SW	NO	YES	YES	REMOTE COUPLER	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	Q3A2	NO	MANUAL	WITH ENG. SWITCH, WITH VOL. SW	NO	YES	NO	STOP SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	WITHOUT	DEFLECTOR	
GX440IU	Q4AA	NO	MANUAL	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	NO	STOP SWITCH	SWITCH MODE 1	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	3 TERMINAL HARNESS	DEFLECTOR	
GX440IU	Q5A2	NO	MANUAL	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	NO	STOP SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	Q5EN	3 A	MANUAL	W/O ENG. SWITCH, W/O VOL. SW	YES	YES	NO	REMOTE COUPLER	AUTOTHROTTLE 1	YES	YES	NO	6.3X6.3X43	1 INCH	INT 3/8-24UNF	6P COUPLER HARNESS	DEFLECTOR	Negri Autothrottle 3600 rpm, remote stop switch
GX440IU	SPA2	20 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	VOLUME 1400-3600 RPM	YES	YES	NO	7 X 7 X 33	25 MM	INT M8 X 1.25	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	VAA4	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	SWITCH MODE 1	YES	YES	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	WITHOUT	DEFLECTOR	Switch 1: OFF 3000, ON 3600	
GX440IU	VCAA	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	SWITCH MODE 3	YES	YES	YES	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	3 TERMINAL HARNESS	DEFLECTOR	
GX440IU	VCLE	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	NO	YES	COMBINATION SWITCH	SWITCH MODE 3	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	3 TERMINAL HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile muffler, low profile aircleaner Low noise cooling fan Switch mode 3: 2000, 3000, 3600
GX440IU	VDAA	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	YES	COMBINATION SWITCH	SWITCH MODE 4	YES	YES	YES	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	VDLF	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	NO	YES	COMBINATION SWITCH	SWITCH MODE 4	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile muffler, low profile aircleaner Low noise cooling fan Switch mode 4: 3000, 3600, 2500-3600
GX440IU	VDL6	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	NO	YES	COMBINATION SWITCH	SWITCH MODE 4	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile muffler, low profile aircleaner Low noise cooling fan Switch mode 4: 3000, 3600, 2500-3600
GX440IU	VDMF	3 A	AUTO CHOKE	WITH ENG. SWITCH, W/O VOL. SW	NO	NO	YES	COMBINATION SWITCH	SWITCH MODE 4	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile aircleaner No muffler Switch mode 4: 3000, 3600, 2500-3600
GX440IU	VHAA	3 A	AUTO CHOKE	W/O ENG. SWITCH, W/O VOL. SW	NO	YES	YES	REMOTE COUPLER	SWITCH MODE 4	YES	YES	YES	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	
GX440IU	VHMF	3 A	AUTO CHOKE	W/O ENG. SWITCH, W/O VOL. SW	NO	NO	YES	REMOTE COUPLER	SWITCH MODE 4	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile aircleaner No muffler Switch mode 4: 3000, 3600, 2500-3600
GX440IU	V2A4	NO	MANUAL	WITH ENG. SWITCH, W/O VOL. SW	NO	YES	NO	STOP SWITCH	SWITCH MODE 1	YES	YES	YES	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	WITHOUT	DEFLECTOR	Switch 1: OFF 3000, ON 3600
GX440IU	V3AA	NO	MANUAL	WITH ENG. SWITCH, WITH VOL. SW	NO	YES	NO	STOP SWITCH	VOLUME 1400-3600 RPM	YES	YES	YES	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	WITHOUT	DEFLECTOR	
GX440IU	V5L6	NO	MANUAL	WITH ENG. SWITCH, W/O VOL. SW	NO	NO	NO	STOP SWITCH	SWITCH MODE 4	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile muffler, low profile aircleaner Low noise cooling fan Switch mode 4: 3000, 3600, 2500-3600
GX440IU	V9MF	NO	MANUAL	W/O ENG. SWITCH, W/O VOL. SW	NO	NO	NO	REMOTE COUPLER	SWITCH MODE 4	YES	YES	NO	NO	TAP 2 1/4"/FT	INT 5/16-24 UNF	6P COUPLER HARNESS	DEFLECTOR	Low profile variation: no fuel tank, low profile muffler, low profile aircleaner No muffler Switch mode 4: 3000, 3600, 2500-3600